US006597634B2

(12) **United States Patent**
O'Brien, Jr. et al.

(10) **Patent No.: US 6,597,634 B2**
(45) **Date of Patent: Jul. 22, 2003**

(54) **SYSTEM AND METHOD FOR STOCHASTIC CHARACTERIZATION OF SPARSE, FOUR-DIMENSIONAL, UNDERWATER-SOUND SIGNALS**

(75) Inventors: **Francis J. O'Brien, Jr.**, Newport, RI (US); **Chung T. Nguyen**, Austin, TX (US)

(73) Assignee: **The United States of America as represented by the Secretary of the Navy**, Washington, DC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/934,343**

(22) Filed: **Aug. 22, 2001**

(65) **Prior Publication Data**

US 2003/0043695 A1 Mar. 6, 2003

(51) **Int. Cl.**[7] **G06F 7/00**
(52) **U.S. Cl.** **367/135**
(58) **Field of Search** 367/135, 901, 367/21; 375/346, 316; 708/200

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,703,906 A * 12/1997 O'Brien et al. 367/21
5,963,591 A * 10/1999 O'Brien et al. 375/346
5,966,414 A * 10/1999 O'Brien, Jr. 375/346
6,397,234 B1 * 5/2002 O'Brien et al. 708/200

OTHER PUBLICATIONS

Rekkas et al.;Three–Dimensional Tracking Using On–Board Measurements; Jul. 1991;IEEE Transactions on Aerospace and Electronic Systems vol. 27, No. 4.*

* cited by examiner

Primary Examiner—Daniel T. Pihulic
(74) *Attorney, Agent, or Firm*—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) **ABSTRACT**

A signal processing system provides and processes a digital signal, converted from to an analog signal, which includes a noise component and possibly also an information component comprising small samples representing four mutually orthogonal items of measurement information representable as a sample point in a symbolic Cartesian four-dimensional spatial reference system. An information processing sub-system receives said digital signal and processes it to extract the information component. A noise likelihood determination sub-system receives the digital signal and generates a random noise assessment of whether or not the digital signal comprises solely random noise, and if not, generates an assessment of degree-of-randomness. The information processing system is illustrated as combat control equipment for undersea warfare, which utilizes a sonar signal produced by a towed linear transducer array, and whose mode operation employs four mutually orthogonal items of measurement information.

6 Claims, 4 Drawing Sheets